

CAROLINA TRAILERS & EQUIPMENT



Pictures are for representational purposes only and may show additional options.

10 Ton Equipment Trailer

Standard Specifications

Framework

Mainframe:	10" WF @ 17#/ft
Crossmembers:	3" Channel on 16" Centers
Flooring:	2" x 8" Pressure-Treated Pine

Undercarriage

Brakes:	Electric, All Wheels
Tires:	(8) LT 235/80R 16LR-E SBR
Wheels:	(8) 8 Hole HD Steel Disc
Axles:	(2) 10,000# Oil Bath

Dimensions

Overall Length:	30'
Overall Width:	102"
Bed:	20'
DoveTail:	5'
Tongue:	5', Cold-Rolled
Ramps:	5' Fold-Over, Bar-Up, Spring Assisted, Adjustable Height
Height:	35" +/- (unloaded height)

Additional Features

Jack:	12,000# Drop Leg
Coupler:	Pintle Ring, Adjustable Height
Rub Rails:	Rub Rails w/Stake Pockets @ 24" Centers
Lighting:	DOT Approved; Recessed & Rubber-Mounted
Wiring:	Sealed Wiring Harness w/7-Way Plug
DOT Conspicuity Tape:	Full Length of Trailer
Access Step:	(1) Driver's Side Step
Tool Tray:	Located in Tongue
Safety Chains:	Heavy Duty Safety Chains
Finish:	Cleaned, Primed, Painted Choice of Standard Colors

AVAILABLE OPTIONS FOR THE 10 TON EQUIPMENT TRAILER (PARTIAL LISTING)

- *Pierced Frame
- *Hydraulic Ramps
- *Bi-Fold Ramps
- *LED Lighting
- *Mid-Span Turn Signals
- *Length
- *2-Speed Landing Gear: Single or Dual
- *D-Rings ILO Rub Rails, Stake Pockets
- *Aluminum Wheels
- *Stainless Steel Simulators
- *Self-Cleaning Angle Dovetail
- *Dovetail w/Traction Bars
- *Roll-Up Dovetail
- *Electric/Hydraulic Brakes
- *Air Brakes
- *Heavy-Duty 10,000# Axles