

# CAROLINA TRAILERS & EQUIPMENT



*Pictures are for representational purposes only and may show additional options.*

## 12 Ton Equipment Trailer

### Standard Specifications

#### **Framework**

Mainframe:	10" WF @ 17#/ft w/Pierced Crossmembers
Crossmembers:	3" Channel on 16" Centers
Flooring:	2" x 8" Pressure-Treated Pine

#### **Undercarriage**

Brakes:	Electric, All Wheels
Tires:	(8) LT 235 80R 16LR-E
Wheels:	(8) 8 Hole HD Steel Disc
Axles:	(2) 12,000# Oil Bath

#### **Dimensions**

Overall Length:	30'
Overall Width:	102"
Bed:	20'
DoveTail:	5'
Tongue:	5', Cold-Rolled
Ramps:	5' Fold-Over, Bar-Up, Spring Assisted
Height:	35" +/- (unloaded height)

#### **Additional Features**

Jack:	12,000# Drop Leg
Coupler:	Pintle Ring, Adjustable Height
Rub Rails:	Rub Rails w/Stake Pockets @ 24" Centers
Lighting:	DOT Approved; Recessed & Rubber-Mounted
Access Step:	(1) Driver's Side Step
Tool Tray:	Located in Tongue
Safety Chains:	Heavy Duty Safety Chains
Finish:	Cleaned, Primed, Painted Choice of Standard Colors

#### **AVAILABLE OPTIONS FOR THE 12 TON EQUIPMENT TRAILER (PARTIAL LISTING)**

- \*Pierced Frame
- \*Hydraulic Ramps
- \*Bi-Fold Ramps
- \*LED Lighting
- \*Mid-Span Turn Signals
- \*Length
- \*2-Speed Landing Gear: Single or Dual
- \*Aluminum Wheels
- \*Stainless Steel Simulators
- \*Self-Cleaning Angle
- \*Roll-Up Dovetail
- \*Electric/Hydraulic Brakes
- \*Air Brakes
- \*D-Rings ILO Rub Rails, Stake Pockets