


CAROLINA TRAILERS & EQUIPMENT



35 Ton Paver

(GVWR: 70,000#)



Framework

Mainframe:	16" @ 40# per ft. WF Beam, Pierced; Arched; Bridged
Crossmembers:	6" @ 12# per foot WF Beam, Full-Formed Gussets @ Inside Frame Crossmembers
Side Rails:	12" Channel
Flooring:	2" Treated Oak, Secured with 3/8" Bolts, Floor Clips

Undercarriage

Axles:	(2) 25,000 # Wide Track, Oil Bath
Suspension:	Hutch 9700 4-Spring Equalizing, w/Adjustable Torque Arms
Brakes:	Air w/ABS & Park Brake
Tires:	(8) 235 x 17.5 SBR 18-PR
Wheels:	(8) 17.5 10-Hole Steel Disc

Dimensions

Load Deck Length:	28'
Upper Deck:	9' w/Treated 2" Oak Floor
Front Slope:	5' Wood (or) Steel w/Traction Bars
Dove Tail:	6' Wood (or) Steel w/Traction Bars
Ramps:	11' x 42" Bifold, w/ Tapered Ends; Hydraulic/Electric Power

Additional Specs

Lighting:	All DOT Approved; Sealed Wiring Harness w/Modular Connections; Recessed & Rubber Mounted LED Lights; Mid-Span Turn Signals
Landing Gear:	Dual 2-speed; 29,000# Side Load/160,000# Vertical Load
Access Step:	(1) Located on Driver Side
Paint:	Sandblasted, Cleaned, Primed & Painted w/Choice of Standard Colors
Tool Tray:	In Upper Deck
D-Rings:	Min. (8) per Side; Heavy Duty Cupped Type (or) Rub Rails w/Stake Pockets; Wide Load Flag Holders
DOT Conspicuity Tape:	Full Length of Trailer

AVAILABLE OPTIONS FOR THE 30 TON TRIAXLE PINTLE HITCH PAVER (Partial Listing)

- *Locking Under Body Toolbox(es)
- *Tire/Wheel Combinations
- *Alcoa Aluminum Wheels: Inside Polished w/Nut Covers
- *Stainless Steel Simulators
- *Ramp Styles & Dimensions
- *Trailer Configurations: Arrangements, Width, Length
- *Front Headboard
- *Winch & Cable
- *Ratchet Track w/Sliding Winches
- *Spare Carrier
- *Bucket Plate
- *Spare Tire & Wheel
- *Inside/Outside Guides (for Track Equipment)
- *Side-Rail Cut-Outs
- *Additional D-Rings
- *Recessed D-Rings in Floor
- *Air Ride Suspension
- *Swing-Out Outriggers
- *Triple Axle
- *Strobe Lights