

**6 TON EQUIPMENT TRAILER
2 AXLE**

FRAME WORK

Main Frame	6" Channel 8.2# per Ft
Crossmembers (Main Frame)	Bottom 5" Channel 5.4# per Ft
Tilt Frame	6" Channel 8.2# per Ft
Crossmembers (Tilt Frame)	3" Channel 4.1# per Ft on 16" Centers
Deck	2" x 8" Oak
Fenders	10" Wide 1/8" Treadplate

UNDERCARRIAGE

2 Axles	6000# 6 Lug EZ Lube Torflex
Brakes	12" x 2" Electric, All Wheels
Tires	235 85R16 LR E
Wheels	6 Lug White Spoke Modular

DIMENSIONS

Length	17' Standard
Width	80 1/2" Between Fenders
Bed Height	26" from Ground
Hitch	Adj Pintle or 2 5/16" Ball (or) 2" Bulldog
Tongue Length	5'
Trailer Weight	3500#
Capacity	12000# GVWR at 50 mph w/ Even Load
Hauling Capacity	8,000#

MISCELLANEOUS

Eight (8) 4" D-Rings	3/8" High Test Safety Chains
10,000# Drop Leg Jack	Breakaway System w/ Battery
DOT Approved Lighting	Wiring in Conduit
Completely Primed and Painted w/ 2 Coats of Industrial Paint	

OPTIONS

2 5/16" Ball Coupler	Adjustable Gooseneck
Partial Tilt	Bed Length
Stake Pockets	Steel Deck
Spare Tire	